


WDQJ340 : 4" BIONIC SQUARE

1000LM-1500LM (20W-30W)



- Uniform, low glare illumination
- 120-277V Input options
- Glare Shields for eye comfort
- Wireless and wired RGBW options available (12W)
- Multiple Beam Spreads and Color Temperatures
- Weep holes for water drainage
- Integral J-box option
- Emergency Back-Pack option
- Available with Type IV/Forward Throw Optics

ORDERING : WDQJ340W-BADJ10-BF45UE-D10-EMAC-T27

WDQJ340

Fixture	Finish	Lumen	Optics (Adjustable)	Optics (Fixed)	Dimming	Emergency Options	LED	Options
---------	--------	-------	---------------------	----------------	---------	-------------------	-----	---------



LINK

Finish	Optics	Dimming	LED
White (RAL 9003) W	<i>Beam Adjustable Fixture</i>	<i>Beam Fixed Fixture</i>	4000K (90 CRI) Blank
Black (RAL 9005) B	<i>Standard Beams</i>	<i>Standard Beams</i>	2700K (90 CRI) -T27
Bronze (RAL 8019) BZ	Wide Flood Blank	Wide Flood Blank	2700K (97 CRI) -T27-C97¹
Silver (RAL 7037) S¹	Narrow Spot -BADJ10	Narrow Spot -BF10	3000K (90 CRI) -T30
Light Silver (RAL 7036) LS¹	Spot -BADJ20	Spot -BF20	3000K (97 CRI) -T30-C97¹
Dark Grey (RAL 7015) DG¹	Flood -BADJ45	Flood -BF45	3500K (90 CRI) -T35
Metallic Gold (RAL 1001) MG¹	<i>CleanBeam™ Option</i>	<i>CleanBeam™ Option</i>	5000K (80 CRI) -T50
Metallic Black (RAL 7021) MB¹	10° Pencil Beam -CBADJ10	10° Pencil Beam -CBF10	RGB+W Control (24VDC) -RGBWV24²

Lumen	Optics	Dimming	LED
2 x 1000LM (20W)	Blank	Non-Dimming (120V)	4000K (90 CRI) Blank
2 x 1500LM (30W)	-L13	ELV and Triac Dimming (120V)	2700K (90 CRI) -T27
		-DIN³	2700K (97 CRI) -T27-C97¹
		0-10V Dimming (120V/277V)	3000K (90 CRI) -T30
		UE-D10³	3000K (97 CRI) -T30-C97¹
		UniDim™ (120V/277V)	3500K (90 CRI) -T35
		UE-DUN³	5000K (80 CRI) -T50
		0-10V 1% Dimming (120V/277V)	RGB+W Control (24VDC) -RGBWV24²
		UE-D10P1³	

Specialty Beams	Emergency Options ⁸	Options
Wall Wash -BFWW	Blank	None Blank
Forward Throw -BFIV	Blank	Black Hexcell -LVR
(Type IV)		Louver
Type IIIS (30° x 60°) -BFII	Blank	Integral Junction Box 1-Entry -JBL, JBR⁵
	Remote	Photocell Sensor -SDL
	Back Pack (Side Mount)	Surge Protector -SRG
	Back Pack (Face Mount)	Cold Weather -CW^{4,6}
	Back Pack (Empty)	Glare Shield (Up) -SHU
	-EMB-FC⁶	Glare Shield (Down) -SHD
	-EMB-BLANK^{6,7}	Glare Shield (Up and Down) -SH

¹ Special Order. Minimum order, extended lead time may apply. Consult factory. (Finish options 50 piece minimum. 10-12 week lead time).

² Remote Power Supplies and Control Gear Required, Available with Wireless Bluetooth or DMX Control. Consult Factory for Details.

³ Standard Driver Starting Temp -10°C/14°F.

⁴ Starting Temp -30°C/-22°F.

⁵ Specify (JBL) left or (JBR) right entry

⁶ (-EMB) is not compatible with (-CW) option.

⁷ Blank EM enclosure available for Non-EM units to provide a seamless design aesthetic when EM enabled products are installed.

⁸ Only available for the Fixed fixture. Emergency options not available on both fixtures.

⁹ Reference Page 4 for (-EMAC) wiring diagram.

SPECIFICATION

Application

This WDJ series bi-directional wall mount luminaire can be used for both interior and outdoor settings. The dual reflector design can be used for both direct downward and indirect upward illumination for new construction or retrofit installations. Typical locations are in residential, commercial, and architectural facades and retail spaces that contain walls and/or columns.

Housing/Arm

Housing and Arm are constructed of one piece rectilinear high grade aluminum extrusions (Alloy 6061<.04% Cu). Faceplate (with flush mounted tempered glass lens) and end caps are of a robust die cast aluminum alloy and are secured to the housing with (4) socket head tamper resistant stainless steel screws and seal the housing (top and bottom) using silicone gaskets. An aluminum alloy mounting plate with a U-bracket installs onto an electrical junction box and secures into the arm with two (2) flat head countersunk phillips head stainless steel screws.

Mounting:

The 4-1/4" square mounting plate with U-bracket installs onto a 3-1/2" or 4" octagonal electrical junction box. For other junction box sizes see installation instructions.

Finish:



A 7-stage electrostatic, polymer process provides an outdoor textured powder coat finish that delivers outstanding durability, superior anti-aging, resistance to corrosion and UV-degradation. Consult factory for Custom Color. (More Information)

Standard Finishes:

White:	RAL 9003 (W)
Silver:	RAL 7037 (S)
Basic Bronze:	RAL 8019 (BZ)
Black:	RAL 9005 (B)

Special Order Finishes:

Light Silver:	RAL 7036 (LS)
Dark Gray:	RAL 7015 (DG)
Metallic Gold:	RAL 1001 (MG)
Metallic Black:	RAL 7021 (MB)

Certifications and Listings:

ETL / cETL Listed to UL1598 and UL8750 standards.

Suitable wet locations. (IP65)

Assembled in USA.

IK08 rated for impact resistance.



SPECIFICATION (Continued)

Caution: LITON recommends use of surge protectors on the power entering LED Housings. Surge damage is not covered by warranty.

Warranty

Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship. Fixture should not be installed in applications with ambient temperature above 50°C/122°F. Doing so will result in reduced lamp life and voided warranty.

Optics

Up and Down multifaceted aluminum reflectors produce low glare illumination with multiple light control options.

Standard Beam: Used for maximum light output and visible field angle.

CleanBeam™: Used for a direct uniform light output with minimized field angle and to enhance building aesthetics.


LED

COB (Chip on Board) singular LED light source provides for smooth, uniform light output, eliminating the imaging produced by multiple LED source optics.

Lumen Maintenance: Lumen Maintenance is a minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Lumen Options (Nominal): 2 x1000lm (20W)
2 x1500lm (30W)

Color Temperature: Binned with 4-step MacAdam ellipses as per ANSI Standard recommendation.



COLOR TEMP:	2700K	3000K	3500K	4000K	5000K
-------------	-------	-------	-------	-------	-------

CRI:	90, 97	90, 97	90	90	80
------	--------	--------	----	----	----

SPECIFICATION (Continued)

RGB+W:



15W RGBW LED Module Illuminates surfaces up to 10 feet away. Used for applications desiring a dynamic color changing effect. RGB+W design allows fine-tuned pastel colors and saturated hues without sacrificing illumination brightness. Can be set for static colors or dynamic shows. Multiple control options available with either Wireless Bluetooth control or DMX 512 remote mounted decoders.

On-site commissioning and programing available.

Consult Factory for Layout Assistance and Lead Times.


COLOR	CCT/WAVELENGTH	POWER
Red	640nm	3.1W
Green	520nm	3.1W
Blue	450nm	3.1W
White	2700K	3.1W



GET IT ON
Google Play



Available on the
App Store



SPECIFICATION (Continued)

Emergency Options

When AC power fails, provides 90 minutes of power to the luminaire. In the event of a power failure, the LED Emergency backup switches to the emergency mode and operates the existing fixture for 90 minutes. The unit contains a battery, charger, and converter circuit in a single enclosure. (-EMB-SD/FC/BLANK) not for use with -CW (Cold Weather) option. Consult factory.


Remote Emergency Back Up (-EMAC)

For installation away from the surface of the building in remote hidden location.


- Hidden Emergency Equipment
 - Must be installed in Dry Locations
 - Wattage package will determine if 25W or 40W battery gets sent; corresponding wiring diagrams below

Not rated for outdoor mounting.



Damp location rated.



Output Power:	25 Watts (Max)
Input Power:	6 Watts (Max)
Emergency Operation:	≥90 minutes
Operating temp:	0°C/32°F to 50°C/122°F
Input Voltage:	100-277 VAC, 50-60Hz
Battery:	High Temp Nickel-Cadmium 48 Hour Recharge 7-10 Year Life Expectancy
Charge Time:	24 hours
Max Distance:	25'
Weight:	3 lbs.
Warranty:	2-year
Surge Protection:	None



Input Voltage:	120-277VAC/60Hz
Output Voltage:	170VDC (120VAC Equivalent)
Wattage:	40W
Switching Time:	<1s
Charging Time:	24h
Operating Time:	90 minutes
Minimum Temperature:	0°C
Maximum Temperature:	50°C
Maximum Lumens:	3500lm



SPECIFICATION (Continued)

BackPack Side Mount (-EMB-SD/FC)

Eliminates need for long runs back to remote emergency battery location. Installs directly on building surface. Ideal for locations wanting same mounting aesthetics for Emergency and Non-Emergency fixtures without the use of remote Emergency power. Can be fed from recessed wall mounted junction box from the back of fixture.

- Wet location rated.
- 120V-347V operation.
- Self diagnostic.
- Integral surge protector for emergency driver only.
- Includes (2) 1/2" NPT knock-outs.
- Optional -EMB-BLANK can be used to maintain a common aesthetic when -EMB-FC are used.




Input Voltage:	120-347 Vac (50/60 Hz)
Input Power:	7 Watts
Output Voltage:	170 V DC
Input Current:	100mA
Output Power:	18W
Surge Protection:	Line-Neutral 3000V
EM Operation:	90 minutes
Charge Time:	24 hour recharge
Ambient Temperature:	0°C to + 50°C (30°F to 122°F)
Weight:	3.7 lb
Rating:	cUL


MODE	TEST SWITCH	INDICATOR STATUS	COMMENT
AC MODE 1	NOT PRESSED	ON (no flash)	EM DRIVER is CHARGING
AC MODE 2	PRESSED ONCE	2s ON THEN 2s OFF (slow flashing)	EM DRIVER is running 30s DIAGNOSTICS test
AC MODE 3	PRESSED TWICE [2s] in sequence	2s ON THEN 2s OFF (slow flashing)	EM DRIVER is running 90min DIAGNOSTICS test
EM MODE 1	NOT PRESSED	2s ON THEN 2s OFF (slow flashing)	EM DRIVER IS OUTPUTING EM CONSTANT POWER LOAD
EM MODE 2	PRESSED ONCE		EM DRIVER IS OFF

When indicator flashes (0.2s) ON and then 0.2s (OFF) quickly or turns off, unit is defective. Contact manufacturer.

20W, 30W



20W, 30W (Dimmer)



NOTE: WHEN LED FIXTURE POWER IS MORE THAN 18W LED FIXTURE MUST BE EQUIPPED WITH 0-10V DIMMABLE DRIVER

SPECIFICATION (Continued)**Additional Options**

Hexcell Louver (-LVR): 3 mm/.125" (size of the cells) - matte black finish, 45° glare cutoff, unframed.



Photocell (-SDL): Allows for energy savings when illumination is not needed during between dawn to dusks. Cuts off power to LED's during day time or in illuminated environments.



Voltage: 120V, 277V
Power Consumption .5W
On/Off Levels: On @ 0-2fc / Off @ 2fc or more
Warranty: 2-Year / 5,000 Cycles
Sensor Size: 3/8"
Rating: UL/cUL

Surge Suppressor (-SRG): Protects driver against surges in line voltage/current (20KV, 1.2/50μS & 10KA, 8/20μS).



Provides a positive indication of end-of-life by opening voltage to the load.
Surge suppressor is a perishable device requiring periodic replacement.
Not a warrantied item.

Electrical

LED Driver: AC 50/60Hz Electronic Direct Current Class 2 driver integrally mounted.
Power Factor > 0.90. See Dimming Section for voltage and wiring.

Minimum Operating Temperature.
Standard: -10°C/14°F

SPECIFICATION (Continued)

Dimming Options

ELV and TRIAC Driver 120V (-DIN):

Compatible with electronic low voltage, and 2-Wire incandescent dimmers. Also known as leading edge, Reverse Phase, Forward Phase dimming. Allows smooth dimming down to 5% depending upon the dimmer's limitations.


0-10V Driver 120V/277V (UE-D10):

Compatible with most existing 0-10V systems. Also known as fluorescent or 5-Wire dimming. Allows smooth dimming down to 5% depending upon the dimmer's limitations. Compatible with daylight harvesting controls.


UniDim™ Driver 120V/277V (UE-DUN):

All in one ELV and TRIAC phase dimming (120V only), and 0-10V dimming (120V/277V). Works with most 3-Wire ELV, 2-Wire incandescent and 120V/277V 5-Wire 0-10V fluorescent dimmers.


Incandescent/Phase Wiring
ELV




TRIAC




0 - 10V Wiring




Incandescent/Phase Wiring
ELV



TRIAC



0 - 10V Wiring




PHOTOMETRY

WDQJ340W-L15UE-DUN (2x1500lm, 30W, 50°, 4000K)

System Power:	29.2W	MULTIPLIERS	
Test Date:	02/2024	CCT	
Beam Angle 50%:	56.8°	2700K :	0.88
Field Angle 10%:	82.3°	3000K :	0.92
Color Temperature:	4141K	3500K :	1.00
CRI:	92.8	4000K :	1.00
Lumens Delivered:	2x1350	Lumens	
CBCP:	1561.63	Blank	0.73
Power Factor:	0.92	-L13	1.00

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
16.0'	17.30'	6.10
14.0'	15.14'	7.97
12.0'	12.98'	10.84
10.0'	10.81'	15.62
8.0'	8.65'	24.40
8.0'	8.65'	24.40
10.0'	10.81'	15.62
12.0'	12.98'	10.84
14.0'	15.14'	7.97
16.0'	17.30'	6.10

WDQJ340W-L15-BADJ10-BF10UE-DUN (2x1500lm, 30W, 15°, 4000K)

System Power:	29.28W	MULTIPLIERS	
Test Date:	02/2024	CCT	
Beam Angle 50%:	14.8°	2700K :	0.88
Field Angle 10%:	33.7°	3000K :	0.92
Color Temperature:	4149K	3500K :	1.00
CRI:	93.2	4000K :	1.00
Lumens Delivered:	2x1494	Lumens	
CBCP:	9836.21	Blank	0.73
Power Factor:	0.93	-L13	1.00

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION


Height	Beam Diameter	FC
16.0'	4.16'	38.42
14.0'	3.64'	50.18
12.0'	3.12'	68.31
10.0'	2.60'	98.36
8.0'	2.08'	153.69
8.0'	2.08'	153.69
10.0'	2.60'	98.36
12.0'	3.12'	68.31
14.0'	3.64'	50.18
16.0'	4.16'	38.42

PHOTOMETRY (Continued)

WDQJ340W-L15-BADJ20-BF20UE-DUN (2x1500lm, 30W, 20°, 4000K)

System Power:	29.26W	MULTIPLIERS	
Test Date:	02/2024	CCT	
Beam Angle 50%:	13.3°	2700K :	0.88
Field Angle 10%:	26.1°	3000K :	0.92
Color Temperature:	4157K	3500K :	1.00
CRI:	92.4	4000K :	1.00
Lumens Delivered:	2x1529	Lumens	
CBCP:	13071.48	Blank	0.73
Power Factor:	0.92	-L13	1.00

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
16.0'	3.73'	51.06
14.0'	3.26'	66.69
12.0'	2.80'	90.77
10.0'	2.33'	130.71
8.0'	1.87'	204.24
8.0'	1.87'	204.24
10.0'	2.33'	130.71
12.0'	2.80'	90.77
14.0'	3.26'	66.69
16.0'	3.73'	51.06

WDQJ340W-L15-BADJ45-BF45UE-DUN (2x1500lm, 30W, 45°, 4000K)

System Power:	29.24W	MULTIPLIERS	
Test Date:	02/2024	CCT	
Beam Angle 50%:	33.8°	2700K :	0.88
Field Angle 10%:	68.8°	3000K :	0.92
Color Temperature:	4167K	3500K :	1.00
CRI:	93.1	4000K :	1.00
Lumens Delivered:	2x1488	Lumens	
CBCP:	3060.90	Blank	0.73
Power Factor:	0.92	-L13	1.00

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION


Height	Beam Diameter	FC
16.0'	9.72'	11.96
14.0'	8.51'	15.62
12.0'	7.29'	21.26
10.0'	6.08'	30.61
8.0'	4.86'	47.83
8.0'	4.86'	47.83
10.0'	6.08'	30.61
12.0'	7.29'	21.26
14.0'	8.51'	15.62
16.0'	9.72'	11.96

PHOTOMETRY (Continued)

WDQJ340W-L15-CBADJ10-CBF10UE-DUN (2x1500lm, 30W, 10°, 4000K)

System Power:	29.24W	MULTIPLIERS	
Test Date:	02/2024	CCT	
Beam Angle 50%:	14.2°	2700K :	0.88
Field Angle 10%:	29.5°	3000K :	0.92
Color Temperature:	4156K	3500K :	1.00
CRI:	93.2	4000K :	1.00
Lumens Delivered:	2x93.5	Lumens	
CBCP:	630.87	Blank	0.73
Power Factor:	0.92	-L13	1.00

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
16.0'	3.99'	2.46
14.0'	3.49'	3.22
12.0'	2.99'	4.38
10.0'	2.49'	6.31
8.0'	1.99'	9.86
8.0'	1.99'	9.86
10.0'	2.49'	6.31
12.0'	2.99'	4.38
14.0'	3.49'	3.22
16.0'	3.99'	2.46