


LRLD6W-QC-T27 - 13W/800lm - 2700K

System Power	:12.6W	Multipliers	
Test Date	:09/2017	4000K	1.48
Beam Angle 50%	:105.4°	3500K	1.30
Field Angle 10%	:149.9°	3000K	1.11
Color Temperature	:2700K	CRI	
CRI	:90	80CRI (Blank)	:0.89
Lumens Delivered	:759lm	90CRI (-C90)	:1.00
CBCP	:301cd	97CRI (-C97)	:1.08

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	15.8'	8.4
7.0'	18.4'	6.1
8.0'	21.0'	4.7
9.0'	23.6'	3.7
10.0'	26.3'	3.0

LRLD6W-QC-T30 - 13W/800lm - 3000K

System Power	:12.7W	Multipliers	
Test Date	:09/2017	4000K	1.33
Beam Angle 50%	:104.5°	3500K	1.66
Field Angle 10%	:149.1°	2700K	0.90
Color Temperature	:3000K	CRI	
CRI	:90	80CRI (Blank)	:0.89
Lumens Delivered	:802.5lm	90CRI (-C90)	:1.00
CBCP	:321cd	97CRI (-C97)	:1.08

CANDELA TABULATION




FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	15.5'	8.9
7.0'	18.1'	6.6
8.0'	20.7'	5.0
9.0'	23.2'	4.0
10.0'	25.8'	3.2

LRLD6W-QC-T40 - 13W/800lm - 4000K

System Power	:13.1W	Multipliers	
Test Date	:09/2017	3500K	1.30
Beam Angle 50%	:105.0°	3000K	0.99
Field Angle 10%	:149.3°	2700K	0.97
Color Temperature	:4000K	CRI	
CRI	:90	80CRI (Blank)	:0.89
Lumens Delivered	:872.92lm	90CRI (-C90)	:1.00
CBCP	:347cd	97CRI (-C97)	:1.08

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
6.0'	15.6'	9.6
7.0'	18.2'	7.1
8.0'	20.9'	5.4
9.0'	23.5'	4.3
10.0'	26.1'	3.5