TYPE PROJECT

CATALOG#

WD2Q340 : 4" SQUARE

2-DIRECTION WALL MOUNT (IP65) 2 x 850 LM





US Assembled | Dark Sky | IP65 | IK08 | RGB+W Option | Intertek

- Now with Integral Emergency Option!
- Durable, corrosion resistant finish
- Emergency back up available
- Dual COB Light Source
- 5-year limited warranty
- Photocell available
- Available with Type IV/Forward Throw Optics

ORDERING : WD2Q340W-BU10-BD45UE-D10-EMAC-T27

WD2Q340

Fixture | Finish | Lumen | Optics | Dimming | Emergency Options | LED | Options

Finish

White	(RAL 9003)	**W**
Silver	(RAL 7037)	**S**
Basic Bronze	(RAL 8019)	**BZ**
Black	(RAL 9005)	**B**
Light Silver	(RAL 7036)	**LS**[3]
Dark Grey	(RAL 7015)	**DG**[3]
Metallic Gold	(RAL 1001)	**MG**[3]
Metallic Black	(RAL 7021)	**MB**[3]

Lumen

2 x 850LM (30W)	**Blank**

Optics

Beam Up	
Standard Beams	
Wide Flood	**Blank**
Narrow Spot	**-BU10**
Spot	**-BU20**
Flood	**-BU45**
CleanBeam™ Option	
10° Pencil Beam	**-CBU02**
Specialty Beams	
Wall Wash	**-BUWW**
Forward Throw (Type IV)	**-BUIV**
Type IIVS (110°x 40°)	**-BUII**

Beam Down	
Standard Beams	
Wide Flood	**Blank**
Narrow Spot	**-BD10**
Spot	**-BD20**
Flood	**-BD45**
CleanBeam™ Option	
10° Pencil Beam	**-CBD02**
Specialty Beams	
Wall Wash	**-BDWW**
Forward Throw (Type IV)	**-BDIV**
Type IIVS (110°x 40°)	**-BDII**

Dimming

Non-Dimming (120V)	**Blank**
0-10V Dimming (120V/277V)	**UE-D10**[5]
ELV and Triac Dimming (120V)	**-DIN**[5]
0-10V 1% Dimming (120V)	**-D10P1**
347V 0-10V Dimming	**-347-D10**[5]

Emergency Options

None	**Blank**
Remote	**-EMAC**[9]
Back Pack (Side Mount)	**-EMB-SD**[9]
Back Pack (Face Mount)	**-EMB-FC**[9]
Back Pack (Empty)	**-EMB-BLANK**[9,10]

LED[1]

4000K (90 CRI)	**Blank**
2700K (90 CRI)	**-T27**
2700K (97 CRI)	**-T27-C97**[3]
3000K (90 CRI)	**-T30**
3000K (97 CRI)	**-T30-C97**[3]
3500K (90 CRI)	**-T35**
5000K (80 CRI)	**-T50**
RGB+W Control (24VDC)	**-RGBWV24**[4]

Options

None	**Blank**
Black Hexcell Louver	**-LVR**
Photocell Sensor	**-SDL**
Surge Protector	**-SRG**
Cold Weather	**-CW**[6,9]
Glare Shield (Up)	**-SHU**
Glare Shield (Down)	**-SHD**
Glare Shield (Up and Down)	**-SH**

[3] Special Order. Minimum order, extended lead time may apply. Consult factory. (Finish options 50 piece minimum. 10-12 week lead time).
[4] Remote Power Supplies and Control Gear Required, Available with Wireless Bluetooth or DMX Control. Consult Factory for Details.
[5] Standard Driver Starting Temp -10°C/14°F.
[6] Starting Temp -30°C/-22°F.
[9] (-EMB) is not compatible with (-CW) option.
[10] Blank EM enclosure available for Non-EM units to provide a seamless design aesthetic when EM enabled products are installed.

347V Input with 0-10V Dimming available. Consult factory for lead times.

(Click for more Information)

View Full Detailed Specification Sheet

2023.12.13